

Shell Kit for Ecolift

Article information

Item no.: 21000S-RBK
GTIN: 4026092097137
Price group: 20

Description

KESSEL shell kit for Ecolift, without sockets, black cover

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating an Ecolift backwater lifting station.

General characteristics

Colour:	black
Type of wastewater:	with sewage
Installation situation:	floor slab installation
Delivery state:	Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)
Inlet max. scoring (DN):	Z-53.2-487
Motor type:	KSM 140
Protection class (pump):	IP 68 (3m/48h)

Dimensions

Net weight:	25 kg
Gross weight:	30,5 kg
Groundwater resistant from lower edge of base section:	3000 mm
Installation depth:	516 - 669 mm
Vertical adjustment:	vertically adjustable upper section
Length:	590 mm
Width:	590 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Nominal pressure (PN):	6
Pressure pipe connection (OD):	40 mm
System:	optional

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Drainage function:

Cover locking:

Load class:

Odour trap:

Cover plate with slotted cover

Polymer

black

366 mm

366 mm

yes

Lock & Lift

L 15 (EN 1253-1)

Multistop