

## The Superflat bathroom drain glued flange, DN 50, tileable



## **Article information**

Item no.: 42701.95 GTIN: 4026092029664 Price group: 10

## **Advantages**

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

## Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant Sealing water height: Discharge rate (l/s) with 20 mm backwater:	30 mm 0,8
General characteristics Nominal size (DN): Outer diameter (OD):	50 50 mm
Dimensions Vertical adjustment: Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Vertical adjustment: Length: Width: Packaging dimension: Packaging dimension:	25 - 90 mm 0,93 kg 1,17 kg 350 mm 350 mm vertically adjustable upper section 332 mm 332 mm length width height
Tank/drain body Number of outlets: Inlet nominal size (DN): Inlet type: Material of drain body:	1 40 mm 1 PP



Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Frame material: Cover locking: Load class: Rim length: Rim material: Upper section material: Odour trap:

tileable cover plate tileable selectable 110 mm 110 mm Stainless steel 14301 placed K 3 (EN 1253-1) 110 mm 110 mm PP included